

# Track Lights

## COB 5-CCT Selectable



### Detail Specifications:

- Finish: White, Black
- Damp Location Rated
- Chip: High Lumen COB, R9 >50, CRI >90
- 2 Step MacAdam Ellipses
- Operating Temperature: -40° - 114° F
- Lens: PMMA Clear Lens
- Average life (L70) of 50,000 hours

### Applications:

- General Track Lighting
- Residential & Multifamily
- Art Galleries, Museums
- Office and Meeting Rooms
- Education, Healthcare, Retail, Hospitality

### Product Information:

- Metal housing and trim for better heat dissipation
- 350° Horizontal Rotation, 90° Vertical Rotation
- Interchangeable beam angles
- For use with H-Type track or surface mount installation
- Select-n-Switch Technology: 5-CCT
- Instant-On to full brightness

### Driver Options:

- Voltage: 120V
- Triac Dimmable Down to 5%
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz
- Built in 2.5Kv Surge Protector
- Flicker Free

### Mounting & Installation:

- Compatible with H-Type single circuit track system
- Surface mount accessory option available for 3/40 J-Box

### Certifications:

- ETL Listed for USA and CA
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017
- IC Rated and ASTM-E283 Air-Tight





Series	Beam Angles	Finish	Mounting	Optional Accessories (Order Separately)	
<b>LED-ATH-10W-5CCT</b> 10W • 1,000lm	<b>30D</b> <sup>1</sup> 30°	<b>WH</b> White	<b>(Blank)</b> H-Type Track	<b>Optic Lens</b>	<b>Surface Mount</b>
<b>LED-ATH-20W-5CCT</b> 20W • 2,000lm	<b>36D</b> <sup>1</sup> 36°	<b>BLK</b> Black	<b>SM</b> Surface Mount	<b>ATH-10W-24D</b> 24° Beam Angle	<b>ATH-SM</b> Surface Mount for 30/40 Jbox
<b>LED-ATH-30W-5CCT</b> 30W • 3,000lm	<b>24D</b> 24°			<b>ATH-10W-60D</b> 60° Beam Angle	
	<b>60D</b> 60°			<b>ATH-20W-24D</b> 24° Beam Angle	
				<b>ATH-20W-60D</b> 60° Beam Angle	
				<b>ATH-30W-24D</b> 24° Beam Angle	
				<b>ATH-30W-60D</b> 60° Beam Angle	

1. • 30D standard on 10W.  
 • 36D standard on 20W & 30W.  
 • 24D & 60D available for all sizes

# Track Lights

## COB 5-CCT Selectable

### FEATURES




# Track Lights

## COB 5-CCT Selectable

### ACCESSORIES



LENS



ATH-SM

### QUICK SHIP MODELS

Model	Voltage	Watts	Lumens	Color	CRI
LED-ATH-10W-5CCT-30D-WH	120V	10w	1000	27/30/35/40/50K	>90
LED-ATH-10W-5CCT-30D-BLK	120V	10w	1000	27/30/35/40/50K	>90
LED-ATH-20W-5CCT-36D-WH	120V	20w	2000	27/30/35/40/50K	>90
LED-ATH-20W-5CCT-36D-BLK	120V	20w	2000	27/30/35/40/50K	>90
LED-ATH-30W-5CCT-36D-WH	120V	30w	3000	27/30/35/40/50K	>90
LED-ATH-30W-5CCT-36D-BLK	120V	30w	3000	27/30/35/40/50K	>90

### OPTIC LENS

Model	Description
ATH-10W-24D	Track Heads: ACRY-Line 24D Optic
ATH-10W-60D	Track Heads: ACRY-Line 60D Optic
ATH-20W-24D	Track Heads: ACRY-Line 24D Optic
ATH-20W-60D	Track Heads: ACRY-Line 60D Optic
ATH-30W-24D	Track Heads: ACRY-Line 24D Optic
ATH-30W-60D	Track Heads: ACRY-Line 60D Optic

### SURFACE MOUNT

Accessory	Description
ATH-SM	Surface Mount for 30/40 Jbox

### TESTED COMPATIBLE DIMMERS

Other dimmers may be compatible but have not been tested. Please contact us for more information.

Lutron	Leviton	Toshiba	Panasonic
DVCL-153P	6674	WDG9001	WN575149
SCL-153P			
LGCL-153P			
MACL-153M			
MSCL-OP153M			
S-600P			
AYCL-153			
DV-600P			