Project:	
Part#:	
Type:	

3CCT Selectable w/ Photocell



Introducing EnVision LED's new Area Barn dusk to dawn flood lights, with three selectable color changing technology. With the flip of a switch on the back of this fixture, easily select between 3000K, 4000K, and 5000K color temps. Suitable for use in wet locations with an IP65 rating and airtight rated fixture, use these eco-friendly instant start and energy saving lights anywhere. Available in a silver or bronze finish with an aluminum housing which is light and soft.

**Certifications:** 

Area Luminaire

Subpart B: 2017

• FCC CFR 47, FCC Part 15,

cUL Listed

#### **Detail Specifications:**

- IP65 Wet Location Rated
- CRI 80 SMD Lumiled LED Chips
- 100-277V Driver, 50/60Hz
- 10KV Surge Protector
- 150° Beam Angle/Type VS Distribution
- THD: 15%
- Operating Temperature: -4°F ~ +124°F
- Storing Temperature: -40°F ~ +185°F
- PF >0.9/Input: .85A/Output: 36-66V DC
- 0-10V Dimmable

### **Applications:**

- Building Perimeters
- Outdoor Area Lighting
- Yard and Dock Areas
- Security Light

#### **Product Information:**

- 3CCT Selectable: 30/40/50K
- Di-cast aluminum housing with pc lens
- No UV emission, no flicker, instant start, no humming



- Dusk to Dawn photocell included

- Average life L70 @ 70,000 hours lumen maintenance



Wattage





• DLC Premium: Outdoor Full-Cutoff

• 5 Year EnVision LED Limited Warranty

**Warranty** 

Silver

Accessories

6



**Product** 

2

Wattage

3

Color

**Finish** 

(Blank)

**BDD-JBX-SLV** BDD-JBX-BZ

Silver J-Box Installation Cover

Warranty

LED-BDD

Area Dusk to Dawn Barn Flood Light 40W 60W 40W (6,200lm) 60W (9.300lm)

**3CCT Selectable:** 30K / 40K / 50K SLV BZ Bronze CS

\*A 7 day lead time will be required for a custom finish **BDD-L-POLE** 

Bronze J-Box Installation Cover Pole Installation Tenon Bracket

(Blank) 5 Year (incl.) 10 Year

Specs and model numbers are subject to change with or without notice





3CCT Selectable w/ Photocell

### **FEATURES**

## **Photocell Included**

Sensor turns light off and on when changing from dusk to dawn



# **Alumnium Housing**

Robust die-cast aluminum housing includes corrosion resistant primer and powder coat finish

### **3CCT Selectable**


Choose between 3 different color temps in one single fixture


Selectable color temps: 3000K/4000K/5000K

# **Instant Start**

No flickering or humming. Light is soft and uniform while being easy on the eyes

3CCT Selectable w/ Photocell







# **Mounting:**


- Easy wall mount with optional J-Box cover
- Easy wall mount with optional tenon pole
- 3 Foot power cord with 0-10V wires

# **PHOTOMETRICS**


Luminous Intensity Distribution Curve








Luminous Intensity Distribution Curve




#### The Average Illuminance Effective Figure



0W 60V

3CCT Selectable w/ Photocell



**Tenon Bracket Dimensions** 

Accessory Model	Accessory Description
BDD-JBX-SLV	Silver J-Box Installation Cover
BDD-JBX-BZ	Bronze J-Box Installation Cover
BDD-L-POLE	Pole Installation Tenon Bracket

