Low Voltage: Half Moon Deck Lights Solid Brass - Architectural Models







Detail Specifications:

- Finish: Öil Rubbed Bronze or Matte Black
- · Housing: Corrosion Resistant Solid Brass
- Lamp Type:G4 Bulbs 12V (not included)
- 35W Halogen Max
- LED bulbs available
- IP Rating: Wet Location IP65
- · Lens: Clear glass

Applications:

- Landscape
- Walkways & Pathways
- Security Lighting
 Hospitality, Multi-Family
- Outdoor Corridors
- General Accent Lighting
- · Residential, Commercial

Product Information:

- Heat resistant glass lens
- Fully adjustable knuckle for precise control
- Water tight silicone ring for waterproofing
- Packaging: Retail color box
- Master box quantity: 40pcs.

Driver Options:

· Compatible with 12V Low Voltage Drivers

- Mounting & Installations:
 Wire: 6' (72") SPT-1W 18 gauge wire lead
- Surface Mount

Warranty:

Lifetime Anti-Corrosion Warranty

Models

DL-BR-ORB-12V Oil Rubbed Bronze DL-BR-MBL-12V Matte Black

1 Bulb Option (Not Included)

LED-G4WP-1.5W-SW

LED-G4WP-1.5W-WW 3000K

LED-G4WP-1.5W-CW

LED-G4WP-2.5W-SW

LED-G4WP-2.5W-WW

LED-G4WP-2.5W-CW

4000K LED-G4WP-3.5W-SW

LED-G4WP-3.5W-WW

LED-G4WP-3.5W-CW


4000K


Specs and model numbers are subject to change with or without notice. Customization of product is available.

FEATURES



DIMENSIONS





ACCESSORIES





Model	Voltage	Finish	Bulb
DL-BR-ORB-12V	12V	Oil Rubbed Bronze	LED-G4WP
DL-BR-MBL-12V	12V	Matte Black	LED-G4WP

BULBS

Model	Voltage	Watts	Lumens	Color
LED-G4WP-1.5W-SW	12V AC/DC	1.5w	110	2700k
LED-G4WP-1.5W-WW	12V AC/DC	1.5w	110	3000k
LED-G4WP-1.5W-CW	12V AC/DC	1.5w	110	4000k
LED-G4WP-2.5W-SW	12V AC/DC	2.5w	210	2700k
LED-G4WP-2.5W-WW	12V AC/DC	2.5w	210	3000k
LED-G4WP-2.5W-CW	12V AC/DC	2.5w	210	4000k
LED-G4WP-3.5W-SW	12V AC/DC	3.5w	280	2700k
LED-G4WP-3.5W-WW	12V AC/DC	3.5w	280	3000k
LED-G4WP-3.5W-CW	12V AC/DC	3.5w	280	4000k