Project:	 1
Part#:	 į
Type:	 i

4" SnapTrim Adjustable Downlight

5CCT Selectable: 27/30/35/40/50K



Detail Specifications:

• IP65 Wet Location Rated • CRI >93 COB LED Chip, R9>50

• 40° Beam Angle

• Input Voltage: 120V (108-132V Range)

• Operating Temperature: 0°F ~ +113°F

• Triac and ELV Dimmable down to 5%

2.5kV Ringwave Surge Protection

Cut Out Dimension: 4-1/4"

EnVision LED has developed a line of 4" SnapTrim Downlights that eliminates the need for a can. The external remote junction box mounts inside the ceiling and the fixture is IC Rated. By reducing material cost and installation time, the EnVision SnapTrim is the ideal retrofit or new construction recessed lighting solution yet. Simply cut a hole in the ceiling, power the J-Box to the wall switch, and "snap" the trim flush. Now available with 5CCT color changing technology! Switch from 27K, 30K, 35K, 40K, and 50K with the flick of a switch!

- Residential or Commercial Downlighting ETL Listed for USA and CA
- New Construction or Remodel use
- General recessed lighting
- Drywall, drop ceiling, sloped ceiling

Product Information:

- 5CCT Selectable: 27/30/35/40/50K
- · Available in white, black, and brushed nickel finish
- SnapTrim Canless: Spring clips with remote j-box eliminates can
- Optional Emergency Backup Available: delivers full lumens in EM mode
- L70 @ 50,000 Hours lumen maintenance
- 360° Adjustable gimbal with 30° tilt
- tension clip springs clamp into 1/2" to 1.5" thick ceiling
- built in (3 in / 3 out)
- New construction rough-in plate or mounting plate with joist bars available (See accessories listed below)

Certifications:

- Energy Star Certifies

Whats Included?:

Cut Out Template

• LED Module

Junction Box

- IC Rated and ASTM-E283 Air-Tight
- CA Title 24 JA8-2019 CEC Listed
- FCC CFR 47, FCC Part 15, Subpart B:2017
- 5 Year EnVision LED Limited Warranty

- **Mounting:**
- No can needed in remodel applications,
- Pre-wired junction box with circuit wiring







Mounting Screws

Installation Guide



FEATURES



Hole Cut Size 43/8" (105~108mm)

4" SnapTrim Adjustable Downlight

Selectable CCT: 27/30/35/40/50K

OPTIONAL ACCESSORIES



CUNV-NC-ICAT

New Construction Plate

Makes new construction installation easier. Universal plate compatible for 2'', 4'', 6'' trims with J-Boxes.



C4-JBX-RI 4" Rough-In Plate

Make installation even easier with this rough-in plate.



JBX-JUMP-(4'/10'/20')

Connector Extension Cord

Extension cord in between driver and downlight. Available in 4', 10', 20' lengths.

Accessory Model	Description		
CUNV-NC-ICAT	2/4/6" New Construction Plate		
C4-JBX-RI	4" Rough-In Plate		
JBX-JUMP-4'	4' Connector Extension Cord		
JBX-JUMP-6'	6' Connector Extension Cord		
JBX-JUMP-10'	10' Connector Extension Cord		

DIMMER COMP A TIBILITY						
Brand	Series	Model	Load	Dimmability		
Lutron	Ariadni	AYCL-153P	150W	OK		
	Diva	DV-600PR	600W	OK		
	Diva	DVCL-153P	150W	OK		
	Maestro	MACL-153MH	600W	OK		
	Maestro Wireless	MRF2-6CL	150W	OK		
	Rotary	D-600P	600W	OK		
	Electronic(ELV)	NTELV-300P	600W	OK		
	Skylark	S-600P	600W	OK		
	Skylark Contour	CT-600P	600W	OK		
	Skylark Contour	CTCL-153P	150W	OK		
	Toggler	TG-600P	600W	OK		
	Toggler	TGCL-153P	150W	OK		
Leviton	Sureslide	6633	600W	OK		
	Sureslide Decora	6674	600W	20-100%		
	Trimatron	6602	600W	20-100%		
	ILLVMATECH	IPL06	600W	OK		
Legrand	Adorne	ADTP703TU	700W	20-100%		
	Harmony	H703PTW	700W	OK		
Cooper	Aspire	9540	1000W	ОК		
	Devine	DAL06P	300W	OK		

13" 3^{3/8}"