Project:	
Part#:	
Type:	



Detail Specifications:

• IP65 Wet Location Rated

120V Driver

• PF >0.9

• 40° Beam Angle

• CRI 93 COB LED Chip, R9>50

• Cut Out Dimension: 3-3/8"

Operating Temperature: 0°F ~ +113°F

Triac and ELV Dimmable down to 5%

3" Regressed Downlight Selectable CCT: 27/30/35/40/50K

EnVision LED has developed a line of 3" LED Regressed Adjustable Downlight that eliminates the need for a can. The external remote junction box mounts inside the ceiling and the fixture is IC Rated. EnVisions 3" downlight features a trim-changable module. Trim changing accessories include: bronze round and square, black round and square, and white square. Now available with 5CCT color changing technology, select from 27K, 30K, 35K, 40K, and 50K with the flick of a switch!

Certifications:

• ETL Listed for USA and CA

 IC Rated and ASTM-E283 Air-Tight CA Title 24 JA8-2019 CEC Listed

Energy Star Certifies

Applications:

- Residential or Commercial Lighting
- New Construction or Remodel use
- General recessed lighting

Product Information:

- 5CCT Selectable: 27/30/35/40/50K
- Available in white or black round finish
- SnapTrim Canless: Spring clips with j-box eliminates can
- Optional Emergency Backup Available: delivers full lumens in EM mode
- L70 @ 50,000 Hours lumen maintenance

Mounting:

- No can needed in remodel applications,
- · Pre-wired junction box with circuit wiring

Whats Included?:

- LED Module
- Mounting Screws
- Installation Guide
- New construction rough-in plate or mounting plate with joist bars available (See accessories listed below)



Specs and model numbers are subject to change with or without notice



• FCC CFR 47, FCC Part 15, Subpart B:2017

5 Year EnVision LED Limited Warranty

- Junction Box Cut Out Template
- tension clip springs clamp into 1/2" to
 - 1.5" thick ceiling

built in (3 in / 3 out)

3" Regessed Downlight Selectable CCT: 27/30/35/40/50K

FEATURES

Easy Installation

Simply snap downlight into the hole that has been cut into ceiling for an easy install.

High Quality LEDs

50,000 hour life with a 40° beam angle make these downlights perfect for any construction project.

5CCT Selectable

Slide switch on wire or driver to choose between 27/30/35/40/50K color temps.

Dimmable

Set the mood right with a 5-100% dimming light, which is compatible with most TRIAC/ELV dimmers.

Detachable Color Trims .

Choose between a selection of different changable trims, between round or square black, bronze, and white square.

Hole Cut Size	3 ^{3/8} "	(79.38mm)
---------------	---------------------------	-----------

3" Regessed Downlight Selectable CCT: 27/30/35/40/50K

Accessory Model	Description
CUNV-NC-ICAT	2/4/6" New Construction Plate
C4-JBX-RI	4" Rough-In Plate
JBX-JUMP-4'	4' Connector Extension Cord
JBX-JUMP-6'	6' Connector Extension Cord
JBX-JUMP-10'	10' Connector Extension Cord

	DIMMER COMPATIBILITY						
	Brand	Series	Model	Load	Dimmability		
	Lutron	Ariadni	AYCL-153P	150W	ОК		
		Diva	DV-600PR	600W	ОК		
		Diva	DVCL-153P	150W	ОК		
		Maestro	MACL-153MH	600W	ОК		
		Maestro Wireless	MRF2-6CL	150W	ОК		
		Rotary	D-600P	600W	ОК		
rith		Electronic(ELV)	NTELV-300P	600W	OK		
		Skylark	S-600P	600W	ОК		
		Skylark Contour	CT-600P	600W	ОК		
		Skylark Contour	CTCL-153P	150W	ОК		
		Toggler	TG-600P	600W	OK		
		Toggler	TGCL-153P	150W	OK		
	Leviton	Sureslide	6633	600W	ОК		
		Sureslide Decora	6674	600W	20-100%		
		Trimatron	6602	600W	20-100%		
		ILLVMATECH	IPL06	600W	ОК		
	Legrand	Adorne	ADTP703TU	700W	20-100%		
		Harmony	H703PTW	700W	ОК		
j	6	Aspire	9540	1000W	ОК		
	Cooper	Devine	DAL06P	300W	ОК		

OPTIONAL ACCESSORIES



New Construction Plate Makes new construction installation

easier. Universal plate compatible for 2'', 4'', 6'' trims with J-Boxes.



C4-JBX-RI 4" Rough-In Plate Make installation even easier with this rough-in plate.



JBX-JUMP-(4'/10'/20') Connector Extension Cord Extension cord in between driver and downlight. Available in 4', 10', 20' lengths.



