| Project: | |
|----------|--|
| Part#: | |
| Туре: | |





Detail Specifications:

- IP65 Wet Location Rated
- CRI 93 COB LED Chip, R9>50
- 120V Driver
- 40° Beam Angle
- Operating Temperature: 0°F ~ +113°F
- PF >0.9
- Cut Out Dimension: 3-3/8"
- Triac and ELV Dimmable down to 5%

3" Regressed Downlight Selectable CCT: 27/30/35/40/50K

EnVision LED has developed a line of 3" LED Regressed Adjustable Downlight that eliminates the need for a can. The external remote junction box mounts inside the ceiling and the fixture is IC Rated. EnVisions 3" downlight features a trim-changable module. Trim changing accessories include: bronze round and square, black round and square, and white square. Now available with 5CCT color changing technology, select from 27K, 30K, 35K, 40K, and 50K with the flick of a switch!

Applications:

- Residential or Commercial Lighting
- New Construction or Remodel use
- General recessed lighting

Product Information:

- 5CCT Selectable: 27/30/35/40/50K
- Available in white or black round finish
- SnapTrim Canless: Spring clips with j-box eliminates can
- Optional Emergency Backup Available: delivers full lumens in EM mode
- L70 @ 50,000 Hours lumen maintenance

Mounting:

- No can needed in remodel applications, tension clip springs clamp into 1/2" to 1.5" thick ceiling
- · Pre-wired junction box with circuit wiring built in (3 in / 3 out)
- New construction rough-in plate or mounting plate with joist bars available (See accessories listed below)

Certifications:

- ETL Listed for USA and CA
- Energy Star Certifies

Whats Included?:

Cut Out Template

• LED Module

Junction Box

- IC Rated and ASTM-E283 Air-Tight
- CA Title 24 JA8-2019 CEC Listed
- FCC CFR 47, FCC Part 15, Subpart B:2017
- 5 Year EnVision LED Limited Warranty

Finish _ Accessory _ 1 Product 2 Size/Watts 6 Color Finish **EMB** Warranty Accessory LED-DLJBX-ADJ-3RG 3-8W 3 Inch **5CCT** 27/30/35/40/50K WH-R White Round (Blank) None (Blank) 5 Years (incl.) None (Blank) 8W / 600 lm **BLK-R** Black Round CUNV Universal Mounting Plate **EMB** Emergency 10 Years C4-JBX-RI 4"Rough In Plate Backup

Specs and model numbers are subject to change with or without notice

EXT-6

EXT-10



6'Extension Cable

10'Extension Cable







Mounting Screws

• Installation Guide



FEATURES

Easy Installation

Simply snap downlight into the hole that has been cut into ceiling for an easy install.

High Quality LEDs

50,000 hour life with a 40° beam angle make these downlights perfect for any construction project.

5CCT Selectable

Slide switch on wire or driver to choose between 27/30/35/40/50K color temps.

Dimmable

Set the mood right with a 5-100% dimming light, which is compatible with most TRIAC/ELV dimmers.

Detachable Color Trims

Choose between a selection of different changable trims, between round or square black, bronze, and white square.

Hole Cut Size **3**3/8" **(79.38mm)**

3" Regessed Downlight

Selectable CCT: 27/30/35/40/50K

OPTIONAL ACCESSORIES



CUNV-NC-ICAT

New Construction Plate

Makes new construction installation easier. Universal plate compatible for 2'', 4'', 6'' trims with J-Boxes.



C4-JBX-RI 4" Rough-In Plate

Make installation even easier with this rough-in plate.



JBX-JUMP-(4'/10'/20')

Connector Extension Cord

Extension cord in between driver and downlight. Available in 4', 10', 20' lengths.

| Accessory Model | Description | | | |
|-----------------|-------------------------------|--|--|--|
| CUNV-NC-ICAT | 2/4/6" New Construction Plate | | | |
| C4-JBX-RI | 4" Rough-In Plate | | | |
| JBX-JUMP-4' | 4' Connector Extension Cord | | | |
| JBX-JUMP-6' | 6' Connector Extension Cord | | | |
| JBX-JUMP-10' | 10' Connector Extension Cord | | | |

| DIMMER COMP A TIBILITY | | | | | |
|-------------------------------|------------------|------------|-------|-------------|--|
| Brand | Series | Model | Load | Dimmability | |
| Lutron | Ariadni | AYCL-153P | 150W | OK | |
| | Diva | DV-600PR | 600W | OK | |
| | Diva | DVCL-153P | 150W | OK | |
| | Maestro | MACL-153MH | 600W | ОК | |
| | Maestro Wireless | MRF2-6CL | 150W | OK | |
| | Rotary | D-600P | 600W | OK | |
| | Electronic(ELV) | NTELV-300P | 600W | OK | |
| | Skylark | S-600P | 600W | ОК | |
| | Skylark Contour | CT-600P | 600W | ОК | |
| | Skylark Contour | CTCL-153P | 150W | OK | |
| | Toggler | TG-600P | 600W | OK | |
| | Toggler | TGCL-153P | 150W | OK | |
| Leviton | Sureslide | 6633 | 600W | OK | |
| | Sureslide Decora | 6674 | 600W | 20-100% | |
| | Trimatron | 6602 | 600W | 20-100% | |
| | ILLVMATECH | IPL06 | 600W | OK | |
| Legrand | Adorne | ADTP703TU | 700W | 20-100% | |
| | Harmony | H703PTW | 700W | OK | |
| Cooper | Aspire | 9540 | 1000W | OK | |
| | Devine | DAL06P | 300W | OK | |

DIMENSIONS



