| Project: |  |
|----------|--|
| Part#:   |  |
| Туре:    |  |





# **Detail Specifications:**

- IP65 Wet Location Rated
- CRI 93 COB LED Chip, R9>50
- 120V Driver
- 40° Beam Angle
- Operating Temperature: 0°F ~ +113°F
- PF >0.9
- Cut Out Dimension: 3-3/8"
- Triac and ELV Dimmable down to 5%

# 3" Regressed Downlight Selectable CCT: 27/30/35/40/50K

EnVision LED has developed a line of 3" LED Regressed Adjustable Downlight that eliminates the need for a can. The external remote junction box mounts inside the ceiling and the fixture is IC Rated. EnVisions 3" downlight features a trim-changable module. Trim changing accessories include: bronze round and square, black round and square, and white square. Now available with 5CCT color changing technology, select from 27K, 30K, 35K, 40K, and 50K with the flick of a switch!

#### **Applications:**

- Residential or Commercial Lighting
- New Construction or Remodel use
- General recessed lighting

#### **Product Information:**

- 5CCT Selectable: 27/30/35/40/50K
- Available in white or black round finish
- SnapTrim Canless: Spring clips with j-box eliminates can
- Optional Emergency Backup Available: delivers full lumens in EM mode
- L70 @ 50,000 Hours lumen maintenance

#### **Mounting:**

- No can needed in remodel applications, tension clip springs clamp into 1/2" to 1.5" thick ceiling
- · Pre-wired junction box with circuit wiring built in (3 in / 3 out)
- New construction rough-in plate or mounting plate with joist bars available (See accessories listed below)

#### **Certifications:**

- ETL Listed for USA and CA
- Energy Star Certifies

Whats Included?:

Cut Out Template

• LED Module

Junction Box

- IC Rated and ASTM-E283 Air-Tight
- CA Title 24 JA8-2019 CEC Listed
- FCC CFR 47, FCC Part 15, Subpart B:2017
- 5 Year EnVision LED Limited Warranty

Finish \_ Accessory \_ 1 Product 2 Size/Watts 6 Color Finish **EMB** Warranty Accessory LED-DLJBX-ADJ-3RG 3-8W 3 Inch **5CCT** 27/30/35/40/50K WH-R White Round (Blank) None (Blank) 5 Years (incl.) None (Blank) 8W / 600 lm **BLK-R** Black Round CUNV Universal Mounting Plate **EMB** Emergency 10 Years C4-JBX-RI 4"Rough In Plate Backup 6'Extension Cable EXT-6

Specs and model numbers are subject to change with or without notice

EXT-10



10'Extension Cable







Mounting Screws

Installation Guide



#### **FEATURES**

# **Easy Installation**

Simply snap downlight into the hole that has been cut into ceiling for an easy install.

# **High Quality LEDs**

50,000 hour life with a 40° beam angle make these downlights perfect for any construction project.

#### **5CCT Selectable**

Slide switch on wire or driver to choose between 27/30/35/40/50K color temps.

### **Dimmable**

Set the mood right with a 5-100% dimming light, which is compatible with most TRIAC/ELV dimmers.

## **Detachable Color Trims**

Choose between a selection of different changable trims, between round or square black, bronze, and white square.

Hole Cut Size **3**3/8" **(79.38mm)** 

# 3" Regessed Downlight

Selectable CCT: 27/30/35/40/50K

#### **OPTIONAL ACCESSORIES**



**CUNV-NC-ICAT** 

#### **New Construction Plate**

Makes new construction installation easier. Universal plate compatible for 2'', 4'', 6'' trims with J-Boxes.



C4-JBX-RI 4" Rough-In Plate

Make installation even easier with this rough-in plate.



# JBX-JUMP-(4'/10'/20')

# **Connector Extension Cord**

Extension cord in between driver and downlight. Available in 4', 10', 20' lengths.

| Accessory Model | Description                   |  |  |
|-----------------|-------------------------------|--|--|
| CUNV-NC-ICAT    | 2/4/6" New Construction Plate |  |  |
| C4-JBX-RI       | 4" Rough-In Plate             |  |  |
| JBX-JUMP-4'     | 4' Connector Extension Cord   |  |  |
| JBX-JUMP-6'     | 6' Connector Extension Cord   |  |  |
| JBX-JUMP-10'    | 10' Connector Extension Cord  |  |  |

| DIMMER COMPATIBILITY |                  |            |       |             |  |
|----------------------|------------------|------------|-------|-------------|--|
| Brand                | Series           | Model      | Load  | Dimmability |  |
| Lutron               | Ariadni          | AYCL-153P  | 150W  | OK          |  |
|                      | Diva             | DV-600PR   | 600W  | OK          |  |
|                      | Diva             | DVCL-153P  | 150W  | OK          |  |
|                      | Maestro          | MACL-153MH | 600W  | OK          |  |
|                      | Maestro Wireless | MRF2-6CL   | 150W  | OK          |  |
|                      | Rotary           | D-600P     | 600W  | OK          |  |
|                      | Electronic(ELV)  | NTELV-300P | 600W  | OK          |  |
|                      | Skylark          | S-600P     | 600W  | OK          |  |
|                      | Skylark Contour  | CT-600P    | 600W  | OK          |  |
|                      | Skylark Contour  | CTCL-153P  | 150W  | OK          |  |
|                      | Toggler          | TG-600P    | 600W  | OK          |  |
|                      | Toggler          | TGCL-153P  | 150W  | OK          |  |
| Leviton              | Sureslide        | 6633       | 600W  | OK          |  |
|                      | Sureslide Decora | 6674       | 600W  | 20-100%     |  |
|                      | Trimatron        | 6602       | 600W  | 20-100%     |  |
|                      | ILLVMATECH       | IPL06      | 600W  | OK          |  |
| Legrand              | Adorne           | ADTP703TU  | 700W  | 20-100%     |  |
|                      | Harmony          | H703PTW    | 700W  | OK          |  |
| Cooper               | Aspire           | 9540       | 1000W | OK          |  |
|                      | Devine           | DAL06P     | 300W  | ОК          |  |

#### **DIMENSIONS**



