

# Waterproof Junction Box Coupling



JBX-WP-3P  
 JBX-WP-4P  
 JBX-WP-5P

JBX-WP-6P

**Series**

- JBX-WP-3P**
- JBX-WP-4P**
- JBX-WP-5P**
- JBX-WP-6P**

<b>JBX-WP-3P</b>
• SO CORD 3 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR
• VOLTAGE RATING: 450V
• CURRENT RATING: 26A
• MIN WIRE SIZE OD: .5-2.5mm, 10-14mm
• UL/ROHS/TUV/UL94-V2/CE

<b>JBX-WP-4P</b>
• SO CORD 4 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR
• VOLTAGE RATING: 450V
• CURRENT RATING: 26A
• MIN WIRE SIZE OD: .5-2.5mm, 10-14mm
• UL/ROHS/TUV/UL94-V2/CE

<b>JBX-WP-5P</b>
• SO CORD 5 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR
• VOLTAGE RATING: 450V
• CURRENT RATING: 26A
• MIN WIRE SIZE OD: .5-2.5mm, 10-14mm
• UL/ROHS/TUV/UL94-V2/CE

<b>JBX-WP-6P</b>
• SO CORD 6 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR
• VOLTAGE RATING: 450V
• CURRENT RATING: 26A
• MIN WIRE SIZE OD: .3-.5mm, 9-12mm
• UL/ROHS/TUV/UL94-V2/CE

Specs and model numbers are subject to change with or without notice. Customization of product is available.