

Waterproof Junction Box Coupling



JBX-WP-3P
 JBX-WP-4P
 JBX-WP-5P

JBX-WP-6P

Series

- JBX-WP-3P**
- JBX-WP-4P**
- JBX-WP-5P**
- JBX-WP-6P**

JBX-WP-3P
<ul style="list-style-type: none"> • SO CORD 3 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR • VOLTAGE RATING: 450V • CURRENT RATING: 26A • MIN WIRE SIZE OD: .5-2.5mm, 10-14mm • UL/ROHS/TUV/UL94-V2/CE

JBX-WP-4P
<ul style="list-style-type: none"> • SO CORD 4 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR • VOLTAGE RATING: 450V • CURRENT RATING: 26A • MIN WIRE SIZE OD: .5-2.5mm, 10-14mm • UL/ROHS/TUV/UL94-V2/CE

JBX-WP-5P
<ul style="list-style-type: none"> • SO CORD 5 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR • VOLTAGE RATING: 450V • CURRENT RATING: 26A • MIN WIRE SIZE OD: .5-2.5mm, 10-14mm • UL/ROHS/TUV/UL94-V2/CE

JBX-WP-6P
<ul style="list-style-type: none"> • SO CORD 6 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR • VOLTAGE RATING: 450V • CURRENT RATING: 26A • MIN WIRE SIZE OD: .3-.5mm, 9-12mm • UL/ROHS/TUV/UL94-V2/CE

Specs and model numbers are subject to change with or without notice. Customization of product is available.