Cusp Disk J-Box or E26





30K	3000K		
TRI	30/40/50K		
5-CCT	27/30/35/40/50K		

WH	WHITE FINISH
BZ	BRONZE FINISH
BLK	BLACK FINISH
BN	BRUSHED NICKEL FINISH

Project:	Part #:
Type:	











Detail Specifications:

- · Finishes:
- 4 & 6": White, Bronze, Black, Brushed Nickel - 8": White
- IP Rating: Wet Location
- · Beam Angle: 100°
- Chip: SMD 2835, R9 >50, CRI >90
- · 3 Step MacAdam Ellipses
- Operating Temperature: -40° 114° F
- · Lens: Frosted Acrylic, non-yellowing
- · Housing: Metal
- Average life (L70) of 50,000 hours

Applications:

- · General Recessed Lighting
- Residential & Multifamily
- Office and Meeting Rooms
- · Education, Healthcare, Retail, Hospitality

Product Information:

- AC technology: slim and easy driverless installation
 Ideal for remodel and new construction use
- · Slim and sleek design

Driver Options:

- 120V Triac dimmable down to 5%
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz
- AC Driverless technology
- Flicker Free

Mounting & Installation:

- 30/40 Junction Box (including pancake j-box)
- · 4", 6" Recessed can converter

Certifications:

- ETL Listed for USA and CA
- Energy Star Certified
- CA Title 24 JA8-2022 CEC Listed
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017
- IC Rated and ASTM-E283 Air-Tight
- Closet Rated

Series

LED-CDSK-4-10W-5CCT-WH

650Lm • 27/30/35/40/50K

LED-CDSK-4-10W-5CCT-BZ

650Lm • 27/30/35/40/50K

LED-CDSK-4-10W-TRI-BN

650Lm • 30/40/50K

LED-CDSK-6-15W-5CCT-WH

1,000Lm • 27/30/35/40/50K

LED-CDSK-6-15W-5CCT-BZ

1,000Lm • 27/30/35/40/50K

LED-CDSK-6-15W-5CCT-BLK

1,000Lm • 27/30/35/40/50K

LED-CDSK-6-15W-5CCT-BN

1,000Lm • 27/30/35/40/50K

LED-CDSK-8-27W-5CCT-WH

2,100Lm • 27/30/35/40/50K


Optional Accessories (Order Separately)

Emergency Backup


LED-EMB-25W-HV-2P

For fixtures up to 25W

Specs and model numbers are subject to change with or without notice. Customization of product is available.



DIMENSIONS



Cusp Disk J-Box or E26



CDSK-4-CLIP



CDSK-6-CLIP

Model	Voltage	Watts	Lumens	Color	CRI
LED-CDSK-4-10W-5CCT-WH	120V	10w	650	27/30/35/40/50K	>90
LED-CDSK-4-10W-5CCT-BZ	120V	10w	650	27/30/35/40/50K	>90
LED-CDSK-4-10W-TRI-BN	120V	10w	650	30/40/50k	>90
LED-CDSK-6-15W-5CCT-WH	120V	15w	1000	27/30/35/40/50K	>90
LED-CDSK-6-15W-5CCT-BZ	120V	15w	1000	27/30/35/40/50K	>90
LED-CDSK-6-15W-5CCT-BN	120V	15w	1000	27/30/35/40/50K	>90
LED-CDSK-6-15W-5CCT-BLK	120V	15w	1000	27/30/35/40/50K	>90
LED-CDSK-8-27W-5CCT-WH	120V	27w	2100	27/30/35/40/50K	>90

BATTERY BACKUP

Accessory	Description
LED-EMB-25W-HV-2P	Up to 25W fixtures



LED-EMB-25W-HV-2P

TESTED COMPATIBLE DIMMERSOther dimmers may be compatible but have not been tested. Please contact us for more information.

Lutron
PD-6WCL
DVCL-153P
CTCL-153P
MACL-153
LECL-153P