

# LED Corn Bulbs

## 3-CCT & 3-Power Selectable



LED-CRN-3M36-TRI-E26



LED-CRN-3M36-TRI-EX39



LED-CRN-3M54-TRI-E26



LED-CRN-3M54-TRI-EX39



LED-CRN-3M80-TRI-EX39



LED-CRN-3M120-TRI-EX39

The EnVision corn light allows the end user to light an area in a full 360° spectrum. The lamp includes an internal driver with a 4kV surge protector, and has a universal input voltage of 120-277v. The light turns on instantly, and is not affected by frequent on/off switching. With 3 different color temperatures and 3 wattages to swap from, it's like having nine SKU's all in one.

### Detail Specifications:

- Water Resistant
- 3-CCT Selectable 30/40/50K
- Beam Angle: 360° Spectrum
- 4kV Surge Protector
- 3 Step MacAdam Ellipses
- Operating Temperature: -40° - 114° F
- Lens: Clear COB
- Average life (L70) of 50,000 hours

### Applications:

- Residential/Commercial Lighting
- Outdoor/Garden Lighting
- Warehouse/Garage Lighting

### Product Information:

- Switch between 30/40/50K color temps
- Also switch between 3 different wattage types
- Includes 4kV surge protection
- 120-277V with ballast bypass
- DLC Listed on EX39 Base Only
- 50,000 life hours

### Certifications:

- UL Certified
- Energy Star Certified
- 5 Year Limited Warranty
- IP65 Rated

### Series

- LED-CRN-3M36-TRI-E26**  
36/27/18w
- LED-CRN-3M36-TRI-EX39**  
36/27/18w
- LED-CRN-3M54-TRI-E26**  
54/45/36w
- LED-CRN-3M54-TRI-EX39**  
54/45/36w
- LED-CRN-3M80-TRI-EX39**  
80/63/54w
- LED-CRN-3M120-TRI-EX39**  
120/100/80w

### Optional Accessories (Order Separately)

- |                                   |  |
|-----------------------------------|--|
| <b>Sensor</b>                     | <b>Remote Control</b>                          |
| <b>HB01DMS-A</b><br>Motion Sensor | <b>HB03R</b><br>Remote for<br>HB01DMS-A Sensor |

# LED Corn Bulbs

## 3-CCT & 3-Power Selectable

### FEATURES



### 3-CCT Selectable




### 3-Power Selectable



**E26 Base**  
Standard Lamp Base



**EX39 Base**  
Larger & Wider Tip Base




**Optional Motion + Daylight Sensor**  
Only available for 3M80 & 3M120 Bulbs

*Specs and model numbers are subject to change with or without notice.*


# LED Corn Bulbs

## 3-CCT & 3-Power Selectable

### DIMENSIONS




LED-CRN-3M36-TRI-E26



LED-CRN-3M36-TRI-EX39



LED-CRN-3M54-TRI-E26



LED-CRN-3M54-TRI-EX39



LED-CRN-3M80-TRI-EX39



LED-CRN-3M120-TRI-EX39



**HB03R**  
Controller for  
HB01DMS-A



**HB01DMS-A**  
Bi Level Motion Sensor and  
Daylight Harvesting Sensor

Model	Voltage	Watts	Lumens	Color
LED-CRN-3M36-TRI-E26	120-277V	18/27/36w	145lm/w	50/40/30k
LED-CRN-3M36-TRI-EX39	120-277V	18/27/36w	145lm/w	50/40/30k
LED-CRN-3M54-TRI-E26	120-277V	36/45/54w	145lm/w	50/40/30k
LED-CRN-3M54-TRI-EX39	120-277V	36/45/54w	145lm/w	50/40/30k
LED-CRN-3M80-TRI-EX39	120-277V	54/63/80w	145lm/w	50/40/30k
LED-CRN-3M120-TRI-EX39	120-277V	80/100/120w	145lm/w	50/40/30k

### CONTROLLER

Accessory Model	Description
HB03R	Controller for HB01DMS-A (Controls Multiple)

### SENSOR

Accessory Model	Description
HB01DMS-A	Bi-Level Motion + Daylight Sensor