



M-Line: 3" Edge-Lit Cylinder Up/Down Light

3-CCT w/ Photocell



WATT	LUMENS
10	1,200
20	2,400
30	3,600

Detail Specification:

- Finish: Bronze, Black, White
- IP Rating: Wet Location IP65
- Beam Angle: 60°
- CCT: 30/40/50K Selectable
- Wattage: 30/20/10w
- Lumens: 3,600
- Chip: SMD 2835, R9 >50, CRI >80
- Operating Temperature: -40° - 122° F
- BUG: B2-U2-G2
- Lens: Clear glass with optics
- Average life (L70) of 50,000 hours

Applications:

- Dock and Loading
- Walkways & Pathways
- Parking Lots
- Hospitality, Multi-Family
- Outdoor Corridors
- General Outdoor Lighting
- Residential, Commercial and Industrial

Product Information:

- Sturdy die-cast aluminum housing finished with corrosion free powder coat
- Photocell included on each fixture. Easy disconnect.
- 1.5" STJW 18.3 AWG cable whip included
- Illuminates up and down and edge
- Select-n-Switch Technology: 3-CCT Selectable + 3-Power Selectable
- Instant-On to full brightness

Driver Options:

- UNV: 120-277V 0-10V Dimmable
- Built in 6Kv Surge Protector
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz

Mounting & Installation:

- Mounts to 3 or 4" J-box
- Covers a standard 4" recessed j-box

Certifications:

- UL Listed for USA and CA
- Approved for CA T24
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017

Series

LED-CYE-UD-3-3P30-TRI -

3" Up/Down Cylinder • 30/20/10W

Finish

- BZ**
Bronze
- WH**
White
- BL**
Black

Photocell

- PC

- Photocell is included.
- Easy quick disconnect.
- (PC-3/4-3PIN-LV)

M-Line: 3" Edge-Lit Cylinder Up/Down Light

3-CCT w/ Photocell

FEATURES



DIMENSIONS

