

M-Line: Security Lights

PIR Sensor + Rotating Heads + 59' Range



-BZ



-BL



-WH

WATT	LUMENS
18	1,980
24	2,640
30	3,300

Detail Specification:

- Power: 30/24/18w Selectable
- Lumens: 3,300/2,640/1,980lm Selectable
- Finish: Bronze, White, Black
- IP Rating: Wet Location (IP65)
- Beam Angle: 120°
- CCT: 30/40/50K Selectable
- Chip: SMD 2835, R9 >50, CRI >80
- Operating Temperature: -40° - 122° F
- Lens: PC Lens: Clear acrylic
- Average life (L70) of 50,000 hours

Applications:

- Security Lighting
- Dock and Loading
- Walkways & Pathways
- Hospitality, Multi-Family
- Outdoor Corridors
- General Outdoor Lighting
- Residential & Commercial

Product Information:

- Sturdy die-cast aluminum housing finished with corrosion free powder coat
- Double head design with high lumen output
- Heads rotate up or down & left or right
- PIR Sensor: triggered when motion is detected up to 59'
- Adjust the motion sensor range, daylight sensitivity, & power on time
- Select-n-Switch Technology: 3-CCT + Power Selectable
- Instant-On to full brightness

Driver Options:

- UNV: 120-277V
- Built in 6Kv Surge Protector
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz

Mounting & Installation:

- Mounts to 3 or 4" J-box

Certifications:

- ETL Listed for USA and CA
- Approved for CA T24
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017

Series

- LED-SC2R-3P30-TRI-BZ-PIR**
Bronze
- LED-SC2R-3P30-TRI-BL-PIR**
Black
- LED-SC2R-3P30-TRI-WH-PIR**
White

M-Line: Security Lights

PIR Sensor + Rotating Heads + 59' Range


FEATURES

90°
Up & Down
Rotation



40°
Left & Right
Rotation

180°
Left & Right
Rotation



PIR Sensor				
1 Time	5S	30S	5min.	∞
2 Lux	35-400Lux	5-50Lux	5-20Lux	
3 Range	Low (0-20ft.)	Medium (20-39ft.)	High (39-59ft.)	



3-CCT Selectable
& Wattage Selectable



DIMENSIONS

