Canless Downlights

4" & 6" LED Slim Panels
Fire Rated Series

FIRE RATED • 5CCT SELECT-N-SWITCH • JA8 TITLE 24 COMPLIANT LAMP • ENERGY STAR • ETL Intertek

4"

6"

Detail Specifications:
- Fire Rated: 2 hour fire rating
- Finish: White, Black, Bronze, Brushed Nickel, Custom
- Wet Location Rated
- Beam Angle: 110°
- Chip: SMD 2835, R9 >50, CRI >90
- 3 Step MacAdam Ellipses
- Operating Temperature: -40° - 114° F
- Lens: Acrylic frosted, non-yellowing
- Average life (L70) of 50,000 hours

Applications:
- General Recessed Lighting
- Residential & Multifamily
- Office and Meeting Rooms
- Education, Healthcare, Retail, Hospitality

Product Information:
- 5-CCT Selectable: 27/30/35/40/50K
- Edge-lit technology: reduces glare with even light distribution
- Perfect for shallow ceilings. Only 1.5" space required.
- Metal housing and trim for better heat dissipation
- Standard white round trim included: optional trims available
- Optional emergency backup available: delivers full lumens in EM mode up to 25W
- SnapTrim Canless: Spring clips with remote j-box eliminates can

Driver Options:
- Voltage: 120V
- Triac Dimmable down to 5%
- Built in 2.5Kv Surge Protector
- Flicker Free

Mounting & Installation:
- Cut Out Dimensions:
  - 4": 4-1/4"
  - 6": 6-1/4"
- Optional new construction plate available
- This fixture does not fit into a recessed can
- No can needed in remodel applications, tension clips mount into 1/2" to 1.5" thick ceiling
- Can be removed from below the ceiling for service or replacement
- Pre-wired junction box with circuit wiring built in (3 in / 3 out)

Certifications:
- ETL Listed for USA and CA
- Energy Star Certified
- CA Title 24 JA8-2022 CEC Listed
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017
- IC Rated and ASTM-E283 Air-Tight
- Complies with UL 263, ASTM E119, CAN ULC S101

Series	Emergency	Optional Accessories (Order Separately)			
		Trim	**New Construction Plates**	**Extension Cables**	**Emergency Backup** [1] (field install)
LED-SL-PNL-4R-12W-5CCT-FR-WH 12W • 840lm	**(Blank)** No Emergency Backup	**SLPNL-TRIM-4R-BLK** Black	**CUNV-NC-ICAT-7H** Universal plate w/ hanging bars	**JBX-EXT-6'-TRI** 6' Extension	**LED-EMB-15W-HV-0/10V-2P** Up to 14W fixtures
LED-SL-PNL-6R-15W-5CCT-FR-WH 15W • 1150lm	**EMB** Emergency Backup	**SLPNL-TRIM-4R-BRZ** Bronze	**C4-JBX-RI** 4" Rough in plate	**JBX-EXT-10'-TRI** 10' Extension	**LED-EMB-25W-HV-0/10V-2P** Up to 24W fixtures
		SLPNL-TRIM-4R-BNI Brushed Nickel	**C6-JBX-RI** 6" Rough in plate	**JBX-EXT-12'-TRI** 12' Extension	
		SLPNL-TRIM-6R-BLK Black	**CUNV-JBX-RI-XL** Universal rough in plate. Extra long		
		SLPNL-TRIM-6R-BRZ Bronze			
		SLPNL-TRIM-6R-BNI Brushed Nickel			1. Field installable. Lasts 90 minutes.

4" & 6" LED Slim Panels
Fire Rated Series

FEATURES

🔥 **FIRE RATED**

External J-Box

5-CCT Selectable

Snap Spring

2 1/2" Knockouts

Cable Mount Lock

Fire Rated

DIMENSIONS

4"

12"

1"

1.3"

1/2"

Ø5" Ø3"

12"

3.5"

6"

12"

1.5"

1.3"

1/2"

Ø7" Ø5"

12"

3.5"

4" & 6" LED Slim Panels
## Fire Rated Series

ACCESSORIES

BLK **BRZ** **BNI**

Model	Voltage	Watts	Lumens	Color	CRI
LED-SL-PNL-4R-12W-5CCT-FR-WH	120V	12w	840	27/30/35/40/50K	>90
LED-SL-PNL-6R-15W-5CCT-FR-WH	120V	15w	1150	27/30/35/40/50K	>90

TRIMS

Accessory Model	Description
SLPNL-TRIM-4R-BLK	4" Round Black Trim
SLPNL-TRIM-4R-BRZ	4" Round Bronze Trim
SLPNL-TRIM-4R-BNI	4" Round Brushed Nickel Trim
SLPNL-TRIM-6R-BLK	6" Round Black Trim
SLPNL-TRIM-6R-BRZ	6" Round Bronze Trim
SLPNL-TRIM-6R-BNI	6" Round Brushed Nickel Trim

CUNV-NC-ICAT-7H
Universal Pre-Mounting Plate
13 7/8" x 15 1/8"

CONSTRUCTION PLATES

| Accessory	Description
CUNV-NC-ICAT-7H	1" 2"3" 3.5" 4" 5" 6" Universal Pre-Mounting New Construction Plate
C4-JBX-RI	4" Rough In Plate
C6-JBX-RI	6" Rough In Plate
CUNV-JBX-RI-XL	Universal tough in plate (Extra Long)

C4-JBX-RI
4" Rough In Plate
6 1/2" x 13 1/4"

EXTENSION CABLE

Accessory	Description
JBX-EXT-6'-TRI	6" Extension Cable
JBX-EXT-10'-TRI	10" Extension Cable
JBX-EXT-12'-TRI	12" Extension Cable

C6-JBX-RI
6" Rough In Plate
8 1/2" x 17 1/4"

BATTERY BACK-UP

Accessory	Description
LED-EMB-15W-HV-0/10V-2P	Up to 14W fixtures
LED-EMB-25W-HV-0/10V-2P	Up to 24W fixtures

CUNV-JBX-RI-XL

JBX-EXT
6' / 10' / 12' Extension Cable

LED-EMB-15W-HV-0/10V-2P
LED-EMB-25W-HV-0/10V-2P