



ARCY-Line: Tubular Linear Fixtures

4-CCT Selectable



Detail Specifications:

- Finish: White, custom available
- IP Rating: Damp Location
- Beam Angle: 110°
- Chip: SMD 2835, R9 >50, CRI >80
- Operating Temperature: -4° - 122° F
- Lens: Acrylic Frosted Lens Standard: efficiently emits the light through a high-quality acrylic lens, spreading it evenly and without causing glare
- Average life (L70) of 50,000 hours

Applications:

- Stairwell & Hallways
- Utility & Storage
- Garage Structures
- Office and Meeting Rooms
- Retail
- Commercial and Industrial

Product Information:

- Construction: aluminum housing with frosted lens
- L-Corner connector available (Does not emit light)
- Finished with corrosion free powder coating
- 6' power cord included on each fixture
- Select-n-Switch Technology: 4-CCT Selectable

Driver Options:

- Max Run: 600W off one power feed
- UNV: 100-277V, 0-10V Dimmable
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz
- 3-Power Selectable
- Flicker Free

Mounting & Installation:

- 5-wire 6' power cord is included. 6-wire power cord is included with emergency models
- 6' Canopy suspension kit (1 power feed) must be purchased separately

Certifications:

- UL Listed for USA and CA
- Approved for CA T24
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017

Series	Length & Watt	Light Direction	CCT	Finish ¹	Emergency
LED-TBL	2FT-20W	D	4CCT	WH	Blank
Tubular	20W	Downlight	30/35	White	None
Architectural	2,300LM	Only	40/50K	BL ¹	EMB
Linear	4FT-40W	UD		Black	Emergency
	40W	Up		SLV ¹	Backup
	4,600LM	& Downlight		Silver	
	8FT-80W			Custom ¹	
	80W			View our available	
	9,200LM			custom colors	

1. Standard quick ship finish is white. Other colors are custom finishes.

Optional Accessories (Order Separately)


Round Trim Options Round Trim Options

SK-6FT-I-CP-TH **TBL-L**
 6' Single Wire L-Shape
 White Finish Connector




ARCY-Line: Tubular Linear Fixtures

4-CCT Selectable

FEATURES



DIMENSIONS



Specs and model numbers are subject to change with or without notice. Customization of product is available.

ARCY-Line: Tubular Linear Fixtures

4-CCT Selectable

Suspended or Surface Mounted Linear
Models: Downlight Only

Model	Voltage	Watts	Lumens	Color
LED-TBL-2FT-20W-D-4CCT-WH	120-277V	20w	2,300	50/40/35/30k
LED-TBL-4FT-40W-D-4CCT-WH	120-277V	40w	4,600	50/40/35/30k
LED-TBL-8FT-80W-D-4CCT-WH	120-277V	80w	9,200	50/40/35/30k

Suspended Linear Models: 80% Downlight & 20% Uplight

Model	Voltage	Watts	Lumens	Color
LED-TBL-2FT-20W-UD-4CCT-WH	120-277V	20w	2,300	50/40/35/30k
LED-TBL-4FT-40W-UD-4CCT-WH	120-277V	40w	4,600	50/40/35/30k
LED-TBL-8FT-80W-UD-4CCT-WH	120-277V	80w	9,200	50/40/35/30k

ACCESSORIES

Model	Description
SK-6FT-I-CP-TH	6" Suspension Kit for ATL
TBL-L	L-Shape Connector

L CORNER PATTERNS

