



Work Light High Bay

Linkable Series



Detail Specifications:

- IP Rating: IP64 Water & Dust Resistant
- Beam Angle: 360°
- CCT: 5000K
- Finish: EnVision Orange
- Chip: SMD 2835, R9 >50, CRI >80
- Operating Temperature: -40° - 114° F
- Average life (L70) of 50,000 hours

Applications:

- Temporary Lighting
- Jobsites

Product Information:

- Heavy duty material for hard construction environment
- Omni-directional light distribution
- Instant-On to full brightness
- Lightweight design
- Foldable hook: compact and easy to transport
- Shatter-resistant wire guard on each unit
- On/Off button on each fixture
- Linkable: Plug and play in series
 - 60W: 12 units max run
 - 100W: 8 units max run
 - 150W: 6 units max run
- Includes linkable cord + plug: 18AWG Gauge SJTW
 - 60W: 15ft cord
 - 100W & 150W: 35ft cord

Driver Options:

- 120V
- 6kV Surge protection
- Non-Dimmable
- PF >0.9, 50/60Hz

Mounting & Installations:

- Integrated 18AWG Gauge Cord - 3 prong plug
- Female receptacle on each unit for continuous run

Certifications:

- UL Listed for USA and CA
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017

Series

LED-WKL-60W-50K-15

7,800 Lumens

LED-WKL-100W-50K-35

13,000 Lumens

LED-WKL-150W-50K-35

19,500 Lumens

Specs and model numbers are subject to change with or without notice. Customization of product is available.

FEATURES



DIMENSIONS

