



Work Light String Lights

Linkable Series



Detail Specifications:

- IP Rating: IP65 Water & Dust Resistant
- Beam Angle: 120°
- CCT: 5000K
- Finish: EnVision Orange
- Chip: SMD 2835, R9 >50, CRI >80
- Operating Temperature: -40° - 114° F
- Average life (L70) of 25,000 hours

Applications:

- Temporary Lighting
- Jobsites

Product Information:

- Heavy duty material for hard construction environment
- Omni-directional light distribution
- Instant-On to full brightness
- Lightweight design
- Foldable hook: compact and easy to transport
 - Avoid lost carabiner clips
- Linkable: Plug and play in series
 - 5 Lamp Set: 5 sets max, 250 ft
 - 10 Lamp Set: 3 sets max, 300 ft

Driver Options:


- 120V
- Non-Dimmable
- PF >0.9, 50/60Hz

Mounting & Installations:

- 18AWG Gauge Cord a 3 prong plug
- Prong receptacle on each unit for continuous run

Certifications:

- ETL Listed for USA and CA
- 3 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017



5 Lamp Set



10 Lamp Set

Series

LED-WKL-SL-5-80W-50K
 LED-WKL-SL-10-160W-50K

Qty	Length	Wattage	Lumens	Max Run	MH Equivalent
5 Lamps	50 ft.	80w	10,000	4 Sets/250ft	250W
10 Lamps	100 ft.	160w	20,000	3 Sets/300ft	400W

Specs and model numbers are subject to change with or without notice. Customization of product is available.

Work Light String Lights

Linkable Series

FEATURES



DIMENSIONS

