

## LED Wall Pack Light Instructions

### Application:

Available in industrial lighting, landscape lighting, courtyard, building, hotel, building exterior, etc.

### Caution:


1. Do not use the electric generator to test the LED lamp.
2. Please abide by related country, regional and local law and regulations when install this fixture.
3. Please don't install the fixture when raining to lower the risk of electric shock and avoid the failure.

### Note:


1. To avoid possibility of electrical shock or fire, the installation personnel must have professional electric knowledge.
2. Please wear gloves to avoid injury before installation.
3. If any smoke or spark of the wire happened, please turn off the power immediately and notify relevant personnel.

### Installation I:


1. Turn off the power




2. Remove the rubber plug and loosen 2 screws




3. Remove the 1/2 end cap




4. Peel off the yellow sticker and paste it on the round area of the bottom plate




5. Fix the bottom plate on the round plate




6. Make wiring connection and make sure the good protection



7. Fix the fixture by 2 screws, block up the two holes with rubber plugs




8. Make sure good wiring and screws fastening, then turn on the power




### Installation I:


1. Turn off the power




2. Remove the rubber plug and loosen 2 screws




3. Remove the 1/2 end cap




4. Peel off the yellow sticker and paste it on the round area of the bottom plate




5. Fix the bottom plate on the round plate




6. Make wiring connection and make sure the good protection




7. Fix the fixture by 2 screws, block up the two holes with rubber plugs



8. Make sure good wiring and screws fastening, then turn on the power




Make sure the battery is well connected if the backup driver is needed.




Special functions instruction:


1. Color temperature adjustable
2. The color temperature of the lamp turns to 3000K when the DIP switch is set to 3000K.
3. The color temperature of the lamp turns to 4000K when the DIP switch is set to 4000K.
4. The color temperature of the lamp turns to 5000K when the DIP switch is set to 5000K.



1. Standard wiring: As for the wire color of DIM+ and DIM-, pls check the light label



2. Wiring for fixture equipped with 5W backup driver : As for the wire color of DIM+ and DIM-, pls check the light label



Warning/Avertissement:

MIN 90°F SUPPLY CONDUCTORS

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED

LES FILS D'ALIMENTATION 194 °C MIN

CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS.