LED Outdoor Wall Sconce Installation Instructions




PLEASE READ CAREFULLY AND SAVE THESE INSTRUCTIONS

CAUTION


- 1. TURN OFF ELECTRICAL POWER BEFORE STARTING INSTALLATION OF LIGHT FIXTURE.
- 2. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.
- 3. CAUTION, RISK OF FIRE. CONSULT A QUALIFIED ELECTRICIAN TO ENSURE CORRECT BRANCH CIRCUIT CONDUCTOR.
- 4. FOR EXTERNAL USE ONLY, RECOMMEND APPLYING WATERPROOF SILICONE TO SEAL AROUND TRIM AND CEILING.

GENERAL


ALL ELECTRICAL CONNECTIONS MUST BE IN ACCORDANCE WITH LOCAL AND NATIONAL ELECTRICAL CODE (N.E.C.) STANDARDS. IF YOU ARE UNFAMILIAR WITH PROPER ELECTRICAL WIRING CONNECTIONS, PLEASE HIRE A QUALIFIED ELECTRICIAN. REMOVE THE FIXTURE AND ITS COMPONENTS FROM THE BOX AND MAKE SURE THAT NO PARTS ARE MISSING.




INSTRUCTIONS




1. PRIOR TO INSTALLATION, INSTALL MOUNTING PLATE (INCLUDED)
INTO THE ELECTRICAL BOX WITH MOUNTING SCREWS (INCLUDED).
DRIVE SCREWS COMPETELY TO THE END OF THE JUNCTION BOX.




2. CONNECT SUPPLY WIRES TO WIRES ON FIXTURE WITH WIRE NUTS (INCLUDED). CONNECT WHITE TO WHITE, BLACK TO BLACK, AND COPPER WIRE TO GREEN WIRE AS A GROUNDING CONNECTION.



3. ADJUST LIGHT DIRECTION USING THE UP/FULL/DOWN SWITCH AND DESIRED COLOR USING THE 5-CCT SWITCH TO YOUR DESIRED SETTINGS.



4. CAREFULLY TUCK ALL WIRES
BACK INTO THE JUNCTION BOX.
PUT THE WALL SCONCE OVER
THE MOUNTING PLATE AND MATCH
THE MOUTING HOLES ON THE PLATE
AND THE SCONCE THEN DRIVE
MACHINE SCREW COMPLETELY
TO SECURE



5. TO PREVENT MOISTURE FROM ENTERING
THE ELECTRICAL JUNCTION AND CAUSING
A SHORT.SEAL AROUND THE TOP AND SIDE
PERIMETER BETWEEN THE FIXTURE AND THE
WALL SURFACE WITH WEATHER RESISTANT
CAULKING. THE SPACE AT THE BOTTOM
SHOULD BE LEFT UN-CAULKED TO PREVENT
MOISTURE BUILD UP.